



19HX Saw Chain

SpeedMax™ Cutting System



FASTER. STRONGER. LONGER-LASTING



.404"



.080"

19HX – Chamfer Chisel®

The 19HX chain is optimized for modern high-flow, high-power heads and saw motors for faster cutting speed. It features tall chamfer chisel cutters that combine best-in-class durability with improved chip clearance, to deliver faster and more consistent cuts in all types of wood.

- + A new, taller and more aggressive chamfer chisel cutter is designed to deliver faster cutting speed compared to 18HX.
- + Oregon's largest and thickest .404 components are designed to provide improved strength and superior durability compared to 18HX.
- + Patented saw chain steel provides proven Oregon durability, especially in cold cutting conditions.
- + Blued cutters provide superior corrosion resistance.
- + Use 19HX chain with a rim type sprocket only. Do not use 19HX on a spur type sprocket.



←x→		A	B	C		D
7/32" 5,5 mm	3/16" 4,8 mm	35°	10°	80°	60°	.050" 1.27 mm

① When using an Oregon file guide, ALWAYS hold it level, 0°, flat on the Top Plate.



Left Hand Cutter

597691



Right Hand Cutter

597692



Tie Strap

597693



Preset Tie Strap

597694



Drive Link

597695



Warning:

To reduce the risk of injury or death, use only 19HX presets and tie straps when repairing or joining 19HX chain.